



B5554ANODA_2	
SILVER ANODISED	
Remote CONTROL GEA	R
IP20	
CURRENT: YmA	
VOLTAGE: 12V, 24V	

combined in straight and broken linear runs Can be sealed by Klus in fixed lengths

to achieve an IP65 waterproof rating

24.20mm 21.80mm 26.20mm

Accessories	
00644	FASTENER DP
42520	BLOCKADE ZM
42716	CONNECTOR ZM 90
42719	CONNECTOR ZMPION 135
42718	CONNECTOR ZMPION 90
C0399NA_2	2M TEKNIK-ZM PROFILE RAW
42740	LIPOD COUPLER L90 LIGER 22
42741	LIPOD COUPLER L90PZ LIGER 22
42742	LIPOD COUPLER L90PW LIGER 22
42743	LIPOD COUPLER L135PZ LIGER 22
42744	LIPOD COUPLER L135PW LIGER 22
42745	LIPOD COUPLER L135 LIGER 22
42746	LIPOD COUPLER T135R LIGER 22
42747	LIPOD COUPLER T135L LIGER 22
42748	LIPOD COUPLER T90 LIGER 22
42749	LIPOD COUPLER X90 LIGER 22
42750	LIPOD COUPLER X135 LIGER 22

Components	
17044_2	2M LIGER-22 BLACK COVER
17007_2	2M G-K FROSTED COVER